

D

6038-LW-3P

60x60x38mm(2.36"x2.36"x1.5")



HOUSING Thermoplastic PBT, UL94V-0
IMPELLER Thermoplastic PBT, UL94V-0
BEARING Ball
OPERATING TEMPERATURE -10°C to +70°C
DIELECTRIC STRENGTH 5mA Max. at 500 VAC for 1 minute
INSULATION RESISTANCE 10M Ω min. @500 VDC
WEIGHT 130 g
ROHS COMPLIANCE Yes
IP LEVEL Special IP Rating On Request

60

 mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
D6038V24L-LW-3P	24	1.10	26.4	20600	5.4	138	67.9	1.92	66.6
D6038V24M-LW-3P	24	1.32	31.6	22700	6.6	167	74.9	2.12	69.1
D6038V24H-LW-3P	24	1.52	36.6	24000	7.3	185	79.1	2.24	72.3
D6038V12L-LW-3P	12	2.20	26.4	20600	5.4	138	67.9	1.92	66.6
D6038V12M-LW-3P	12	2.63	31.6	22700	6.6	167	74.9	2.12	69.1
D6038V12H-LW-3P	12	3.05	36.6	24000	7.3	185	79.1	2.24	72.3

DIMENSION



